

# BAR STOCK THERMOWELLS WITH THREAD CONNECTION MODEL : A600, A601, A602



## ORDERING INFORMATION

### BASE MODEL - 1st thru 4th characters

A600 : Straight Bar Stock (Thread Connection Type)

A601 : Tapered Bar Stock (Thread Connection Type)

A602 : Stepped Bar Stock (Thread Connection Type)

### 15th Character-Options

0=None

1=Plug & Chain

### 5th Character- Extension

0= None    1= Extension

### 6th & 7th Characters - Material

AX=S25C	BX=304SS	CX=316SS
DX=304LSS	EX=316LSS	FX=310SS
GX=321SS	HX=446SS	IX=A182F304
JX=Inconel	KX=Hast-C	LX=Monel
MX=Titanium	NX=Tantalum clad(★)	OX=A182F316
PX=304SS+PTFE Lining	QX=316SS+PTFE Lining	RX=304SS+PTFE Coating
SX=316SS+PTFE Coating	TX=Incoloy	UX=A182F22
VX=A182F91	WX=A105	XX=A182F321
YX=A182-F11	ZX=Others	

**Note (★)Not Available for A601 &A602**

### 8th Character- Internal Connection

0=1/2" NPT

1=1/2" PT

2=1/2" PF

### 9th &10th Characters- End Out Dia./Bore Size Character-

A0=14/7	A1=14/9	B0=16/7	B1=16/9	B2=16/10
C0=17/7	C1=17/9	C2=17/10	C3=17/12	D0=19/7
D1=19/9	D2=19/10	D3=19/12	A4=21/10	

### 11th Character- Connection Size

A=1/2" NPT    B=3/4"    C=1"    D=1 1/4"    E=1 1/2"

### 12th Character- Connection Type

A=NPT    B=PT    C=PF

### 13th Character- Insertion Length ("U"-Length)

0=80	1=100	2=150	3=200	4=250	5=300
6=350	7=400	8=450	A=500	B=600	C=700
D=800	E=900	F=1000	Z=Others		

**Note Please choose a code of next higher length if applicable length is not. Actual length shall be specified.**

### 14th Character-Extension Length ("T"-Length)

0=None(MFR.STD)    1=Below 50MM    2=More than 50MM

**Note Actual length shall be specified.**

## A6000BXOBOBA400 SAMPLE ORDERING NUMBER

